



Pakro Kimya Dış Ticaret A.Ş.

0212 659 26 01-02

[www.pakrokimya.com.tr](http://www.pakrokimya.com.tr)



İstoç Ticaret Merkezi Aktem Plaza  
Kat:5 Daire:33 Bağcılar/İstanbul



0212 659 26 03



[Info@pakrokimya.com.tr](mailto:Info@pakrokimya.com.tr)



## High Density Polyethylene

**62107 - I3**

**With UV**

Typical properties	Test method (DIN)	Unit	Value
MFI@190°C, 2.16 kg	DIN 53735	gr/10min	7
Density	DIN 53479	gr/ml	0.962
Notched Impact Strength	DIN 53453	mj/mm <sup>2</sup>	≥2.7
Standard Yellow Index	DIN 6167	-	≤4

❖ For transport and stacking crates, particularly bottle crates

➤ Values shown are averages & are not to be considered as product specifications.

### ❖ Main application & Characteristics:

62107 is a high density polyethylene grade, suitable for mass production injection moulding of articles in rapid shot sequence applications.

#### || Characteristics:

- Low distortion tendency.
- High hardness and rigidity.
- Good toughness.
- Good ESCR

#### || Typical applications are:

- Transport and stacking crates particularly bottle crates.

❖ **62107** is suitable for food contact.