20212 659 26 03 ☑ Info@pakrokimya.com.tr

Product Datasheet

ExxonMobil™ PP1024E4 Polypropylene Homopolymer



Product Description

A medium melt flow rate homopolymer resin designed for general-purpose injection molding.

General						
Availability 1	•	North America				
				General PurposeHigh Flow	High IsotacticSteam Sterilizable	
				CompoundingConsumer Applications	 Medical/Healthcare Applications ² Packaging 	
Appearance		Natural Color				
Form(s)		Pellets				
Processing Method		Injection Molding				
Revision Date		07/01/2017				
Physical		Typical Value	(Enalish)	Typical Value	(SI)	Test Based On
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)		/ 1	g/10 min	/1	g/10 min	ASTM D1238
Density		0.900	g/cm³	0.900	g/cm ³	ASTM D1505
Mechanical	1	Typical Value	(English)	Typical Value	(SI)	Test Based On
Tensile Strength at Yield		Typical value	(English)	Typical value	(51)	ASTM D638
2.0 in/min (51 mm/min)		4950	nsi	34.1	MPa	A31101 D030
Elongation at Yield (2.0 in/min (51	mm/min))	9.9		9.9		ASTM D638
Flexural Modulus - 1% Secant	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
0.051 in/min (1.3 mm/min)		198000	psi	1370	MPa	ASTM D790A
0.51 in/min (13 mm/min)		243000		1670	MPa	ASTM D790B
mpact		Typical Value	(English)	Typical Value	(SI)	Test Based On
Notched Izod Impact (73°F (23°C))		0.51	ft·lb/in	27	J/m	ASTM D256A
		1				
Thermal		Typical Value	(English)	Typical Value	(SI)	Test Based On
Deflection Temperature Under Load (DTUL)		195	°F	90.6	°C	ASTM D648

Legal Statement

at 66psi - Unannealed

Contact your ExxonMobil Chemical Customer Service Representative for potential food contact application compliance (e.g. FDA, EU, HPFB).

Notes

Typical properties: these are not to be construed as specifications.

Effective Date: 07/01/2017 ExxonMobil Page: 1 of 2

¹ Product may not be available in one or more countries in the identified Availability regions. Please contact your Sales Representative for complete Country Availability.

² This product, including the product name, shall not be used or tested in any medical application without the prior written acknowledgement of ExxonMobil Chemical as to the intended use. For detailed Product Stewardship information, please contact Customer Service.

ExxonMobil™ PP1024E4
Polypropylene Homopolyme



For additional technical, sales and order assistance: www.exxonmobilchemical.com/ContactUs

©2022 ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Product Solutions" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Product Solutions Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.

exxonmobilchemical.com