

Pakro Kimya Dış Ticaret A.Ş.

İstoç Ticaret Merkezi Aktem Plaza Kat:5 Daire:33 Bağcılar/İstanbul Product Datasheet ExxonMobil<sup>™</sup> PP4712E1 Polypropylene Homopolymer



Product Description

An easy-processing homopolymer resin designed primarily for oriented film.

General							
Availability <sup>1</sup>	•	Latin America		<ul> <li>North America</li> </ul>			
Features	•	Metallizable					
Uses •		Industrial Applications • Oriented Film				Tobacco Overwrap Flexible     Packaging	
Appearance	•	Natural Color					
Form(s)	-	Pellets					
Processing Method	•	Film Extrusion		<ul> <li>Injection Molding</li> </ul>			
Revision Date	•	01/01/2019					
Physical		Typical Value	(English)	Typical Value	e (SI)	Test Based On	
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)		0.	g/10 min		3 g/10 mi	n ASTM D1238	
Density		0.900	g/cm³	0.900	) g/cm <sup>3</sup>	ExxonMobil Method	
Mechanical		Typical Value	(English)	Typical Value	e (SI)	Test Based On	
Tensile Strength at Yield 2.0 in/min (51 mm/min)		5050	psi	34 8	3 MPa	ASTM D638	
Elongation at Yield (2.0 in/min (5	1 mm/min))	10		1(	) %	ASTM D638	
Flexural Modulus - 1% Secant 0.051 in/min (1.3 mm/min) 0.51 in/min (13 mm/min)		211000 240000			) MPa ) MPa	ASTM D790A ASTM D790B	
		<b>T</b> 1 1 1 1 1					
mpact	-))	Typical Value		Typical Value		Test Based On	
Notched Izod Impact (73°F (23°C	-))	0.66	ft·lb/in	3:	5 J/m	ASTM D256A	
Thermal		Typical Value	(English)	Typical Value	e (SI)	Test Based On	
Deflection Temperature Under Lo at 66psi - Unannealed	bad (DTUL)	198	-	92.4	1 °C	ASTM D648	
Hardness		Tupical \ /alua	(Epolich)	Turpical Value	(CI)	Test Based On	
Rockwell Hardness		Typical Value	(English)	Typical Value		ASTM D785	
		100		108	,	A31101/03	

## Legal Statement

This product, including the product name, shall not be used or tested in any medical application without the prior written acknowledgement of ExxonMobil Chemical as to the intended use. For detailed Product Stewardship information, please contact Customer Service.

Contact your ExxonMobil Chemical Customer Service Representative for potential food contact application compliance (e.g. FDA, EU, HPFB).

## Notes

Typical properties: these are not to be construed as specifications.

<sup>1</sup> Product may not be available in one or more countries in the identified Availability regions. Please contact your Sales Representative for complete Country Availability.

## ExxonMobil™ PP4712E1

Polypropylene Homopolyme

## For additional technical, sales and order assistance: www.exxonmobilchemical.com/ContactUs

©2022 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Product Solutions" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Product Solutions Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.

exxonmobilchemical.com

