

# ExxonMobil™ LLDPE LL 1001 Series

## Linear Low Density Polyethylene Resin



### Product Description

LL 1001 series are LLDPE grades, offering excellent drawdown and puncture resistance combined with high gloss and clarity. They are also frequently used as a blend partner with LDPE resins to improve film properties and processability. Several additive packages are available according to the required surface properties.

### General

Availability <sup>1</sup>	• Africa & Middle East	• Europe
Additive	<ul style="list-style-type: none"> <li>• LL 1001KI: Antiblock: 2500 ppm; Processing Aid: No; Slip: 1000 ppm; Thermal Stabilizer: Yes</li> <li>• LL 1001XV: Antiblock: No; Processing Aid: No; Slip: No; Thermal Stabilizer: Yes</li> <li>• LL 1001KW: Antiblock: 3500 ppm; Processing Aid: No; Slip: 1500 ppm; Thermal Stabilizer: Yes</li> </ul>	
Applications	<ul style="list-style-type: none"> <li>• Agricultural Film</li> <li>• Bag in Box</li> <li>• Barrier Food Packaging</li> <li>• Blown Film</li> <li>• Bread Bags</li> <li>• Food packaging</li> <li>• Form Fill And Seal Packaging</li> <li>• Freezer Film</li> </ul>	<ul style="list-style-type: none"> <li>• Garment Film</li> <li>• General Packaging</li> <li>• Heavy Duty Bags</li> <li>• Ice Bags</li> <li>• Industrial Liners</li> <li>• Industrial Packaging</li> <li>• Lamination Film</li> <li>• Liners</li> </ul>
		<ul style="list-style-type: none"> <li>• Multilayer Packaging Film</li> <li>• Packaging Films</li> <li>• Produce Bags</li> <li>• Refuse Bags</li> <li>• Shoppers</li> <li>• Stand Up Pouches</li> <li>• Trash Bags</li> </ul>
Revision Date	• March 2010	

Resin Properties	Typical Value (English)	Typical Value (SI)	Test Based On
Density	0.918 g/cm <sup>3</sup>	0.918 g/cm <sup>3</sup>	ExxonMobil Method
Melt Index (190°C/2.16 kg)	1.0 g/10 min	1.0 g/10 min	ASTM D1238
Peak Melting Temperature	248 °F	120 °C	ExxonMobil Method

Film Properties	Typical Value (English)	Typical Value (SI)	Test Based On
Tensile Strength at Break MD	8120 psi	56.0 MPa	ASTM D882
Tensile Strength at Break TD	5220 psi	36.0 MPa	ASTM D882
Elongation at Break MD	550 %	550 %	ASTM D882
Elongation at Break TD	850 %	850 %	ASTM D882
Secant Modulus MD	29000 psi	200 MPa	ASTM D882
Secant Modulus TD - 1% Secant	31900 psi	220 MPa	ASTM D882
Dart Drop Impact	90 g	90 g	ASTM D1709A
Elmendorf Tear Strength MD	80 g	80 g	ASTM D1922
Elmendorf Tear Strength TD	450 g	450 g	ASTM D1922

Optical Properties	Typical Value (English)	Typical Value (SI)	Test Based On
Gloss (45°)	48	48	ASTM D2457
Haze	13 %	13 %	ASTM D1003

### Legal Statement

Contact your ExxonMobil Chemical Customer Service Representative for potential food contact application compliance (e.g. FDA, EU, HPFB).

This product is not intended for use in medical applications and should not be used in any such applications.

Typical properties: these are not to be construed as specifications.

© 2010 Exxon Mobil Corporation. To the extent the user is entitled to disclose and distribute this document, the user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers, and other information. You may not copy this document to a Web site. ExxonMobil does not guarantee the typical (or other) values. Analysis may be performed on representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials, or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage, or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no endorsement of any product or process, and we expressly disclaim any contrary implication. The terms, "we", "our", "ExxonMobil Chemical", or "ExxonMobil" are used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates they directly or indirectly steward. ExxonMobil, the ExxonMobil Chemical Emblem, the "Interlocking X" Device, Enable, Exceed, Exact, Exxco, Escorene, Escor, Iotek, NTX, Polybilt, Paxon and Optema are trademarks or service marks of Exxon Mobil Corporation.

# ExxonMobil Chemical ExxonMobil™ LLDPE LL 1001 Series Linear Low Density Polyethylene Resin

---

## Processing Statement

---

The film properties have been measured on 30 µm (1.18 mil) thick films of LL 1001XV (Blow-up ratio : 2.5)

---

## Notes

<sup>1</sup> Product may not be available in one or more countries in the identified Availability regions. Please contact your Sales Representative for complete Country Availability.

---

Typical properties: these are not to be construed as specifications.

© 2010 Exxon Mobil Corporation. To the extent the user is entitled to disclose and distribute this document, the user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers, and other information. You may not copy this document to a Web site. ExxonMobil does not guarantee the typical (or other) values. Analysis may be performed on representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials, or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage, or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no endorsement of any product or process, and we expressly disclaim any contrary implication. The terms, "we", "our", "ExxonMobil Chemical", or "ExxonMobil" are used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates they directly or indirectly steward. ExxonMobil, the ExxonMobil Chemical Emblem, the "Interlocking X" Device, Enable, Exceed, Exact, Exxco, Escorene, Escor, Iotek, NTX, Polybilt, Paxon and Optema are trademarks or service marks of Exxon Mobil Corporation.