

# ExxonMobil LLDPE

**ExxonMobil** Chemical

## LL 6201 SERIES

Wire & Cable Applications Resins

### Description

LL 6201XR/RQ is a C4 Ziegler Natta LLDPE recommended for compounding applications.

Additive Package	Antiblock	Slip	Thermal Stabilizer	Physical Appearance
LL 6201XR	No	No	Yes	Pellets
LL 6201RQ	No	No	Very Low	Coarse Powder

Resin Properties	Test Based On	Typical Value / Unit	
Melt Index	ASTM D1238	50 g/10 min	
Density	ASTM D4703 / D1505	0.926 g/cm <sup>3</sup>	
Peak Melting Temperature	ASTM D3418	123 °C	253 °F
Crystallization Point	ASTM D3418	105 °C	221 °F

Revised 12/03

©2003 ExxonMobil. To the extent the user is entitled to disclose and distribute this document, the user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers, and other information. You may not copy this document to a Web site. ExxonMobil does not guarantee the typical (or other) values. Analysis may be performed on representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials, or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage, or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no endorsement of any product or process, and we expressly disclaim any contrary implication. The terms, "we", "our", "ExxonMobil Chemical", or "ExxonMobil" are used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates they directly or indirectly steward. The ExxonMobil Emblem, the "Interlocking X" Device and ExxonMobil are trademarks of ExxonMobil Corporation.