

Pakro Kimya Dış Ticaret A.Ş.

Vİstoç Ticaret Merkezi Aktem Plaza Kat:5 Daire:33 Bağcılar/İstanbul

LL6630AA

Product Technical Information

LL6630 is a linear low density polyethylene copolymer containing hexene as the comonomer

It is medium rigidity LLDPE grade.

Properties		Test Method	Value	Units
Physical Melt flow rate Condition 4 Conventional Dens Additives: antioxidants	ity	ISO 1133 ISO 1183 Method D	3.5 930	g/10 min kg/m³
January 2010		INEOS of	Published by efins & Polymers Eur	, ope

LL6630AA

Extrusion conditions

LL6630AA can be processed on most standard extrusion equipment. Optimisation may be required

depending on the exact end use requirements.

LL6630AA should be processed on machinery purpose designed for LLDPE. The product is well

stabilized, melt temperatures in the range 240 - 280°C can be used.

Storage

LL6630AA should be stored in a dry and dust free environment at temperatures below 50°C.

Exposure to direct sunlight should be avoided, as this may lead to product deterioration.

Regulatory Information

The product and uses described herein may require global product registrations and notifications for chemical inventory

listings, or for use in food contact or medical devices. For further information, send an email to psnohreg@ineos.com.

Unless specifically indicated, the products mentioned herein are not suitable for applications in the medical Prealth and Safety Information

ምher βንፅፅዬቲ፤ የመሬንድምፅጅው herein may require precautions in handling. The available product health and safety information for

this material is contained in the Material Safety Data Sheet (MSDS) that may be obtained from the website www.ineospolyolefins.com. Before using any material, a customer is advised to consult the MSDS for the product under

Exclusion of drives ility

Although INEOS O&P Europe endeavours to ensure that all information and advice relating to our materials or other

materials howsoever provided to you by INEOS O&P Europe is accurate and up to date, no representation or warranty,

express or implied is made by INEOS O&P Europe as to its accuracy or completeness. All such information and advice is

provided in good faith and INEOS O&P Europe is not, to the maximum extent permitted by law, liable for any **action** data and numerical results howsoever provided to you by INEOS O&P Europe are given in good faith tarket are a result of relying on such information or advice or for any loss or damage, including any **gensealuentiatuos** Data and numerical results are not and shall not be regarded as specifications and as such shifters dow Pyou as a result of taking such action.

Europe is not, to the maximum extent permitted by law, liable for any action that you take as a result of relying on such

thatenearidsreatuatts tomfor your lossponsibilitygie, ensludenthatny NEODSeQ&PhtElulope, israfferiads by revoluitable resultie partakuinter such

potipoose intended and INEOS O&P Europe shall not be responsible for any loss or damage caused by misuse of INEOS

O&P Europe products. To the maximum extent permitted by law, INEOS O&P Europe accepts no liability whatsoever

arising out of the application, adaptation or processing of the products described herein, the use of other materials in lieu

of INEOS O&P Europe materials or the use of INEOS O&P Europe materials in conjunction with such other materials 2010 Published by

INEOS Olefins & Polymers Europe