

ExxonMobil LDPE

Chemical

LD 165 series

Blown Film Resins

ExxonMobil

Description

The LD 165 series are LDPE grades, offering high strength combined with medium optical properties. Two different additive packages are available according to the surface properties (COF) required.

Applications

- heavy duty sacks
- shrink film
- shoppers (LD165AC)
- construction film

Additive Package	Antiblock	Slip	Thermal Stabilizer
LD 165BW1	No	No	Yes
LD 165AC	450 ppm	500 ppm	Yes

Resin Properties	Test Based On	Typical Value / Unit	
Melt Index	ASTM D1238	0.33 g/10 min	
Density	ASTM D2839 / D1505	0.922 g/cm ³	
Peak Melting Temperature	ASTM D3418	109 °C	228 °F
Crystallization Point	ASTM D3418	96 °C	205 °F

Film Properties				
Tensile Strength	MD	ASTM D882	23 MPa	3350 psi
	TD		23 MPa	3350 psi
Elongation @ Break	MD	ASTM D882	490 %	
	TD		620 %	
1% Secant Modulus	MD	ASTM D882	240 MPa	35000 psi
	TD		260 MPa	37500 psi
Haze		ASTM D1003	11 %	
Gloss, 60° angle		ASTM D2457	8 %	
Dart Drop Impact, A/Face		ASTM D1709	2.2 g/μm	56 g/mil
Elmendorf Tear Strength	MD	ASTM D1922	3.0 g/μm	76 g/mil
	TD		5.0 g/μm	127 g/mil

Film properties have been measured on a 150 μm (5.9 mil) thick blown film of LD 165BW1 (BUR = 1.5)

LD 165 series can - in principle - be used in food contact applications in various EU Member States and in the USA (FDA). Migration or use limitations may apply. Please contact your ExxonMobil Chemical representative for more detailed information and/or actual compliance certification documents for the specific grade of interest.

Revised 12/03

©2003 ExxonMobil. To the extent the user is entitled to disclose and distribute this document, the user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers, and other information. You may not copy this document to a Web site. ExxonMobil does not guarantee the typical (or other) values. Analysis may be performed on representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials, or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage, or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no endorsement of any product or process, and we expressly disclaim any contrary implication. The terms, "we", "our", "ExxonMobil Chemical", or "ExxonMobil" are used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates they directly or indirectly steward. The ExxonMobil Emblem, the "Interlocking X" Device and ExxonMobil are trademarks of ExxonMobil Corporation.