

Technical Data Sheet

Moplen EP332K

Polypropylene, Impact Copolymer

Product Description

Moplen EP332K is a polypropylene impact copolymer with an optimized balance of stiffness and toughness, high impact strength at low temperature, low warpage and good thermal ageing stability. Typical customer applications are injection molding of toys, crates, appliances housing, and general housewares.

Pakro Kimya Dış Ticaret A.Ş.

İstoç Ticaret Merkezi Aktem Plaza Kat:5 Daire:33 Bağcılar/İstanbul

Regulatory Status

For regulatory compliance information, see Moplen EP332K Product Stewardship Bulletin (PSB) and Safety Data Sheet (SDS).

	Commercial: Active					
Availability	Africa-Middle East; Asia-Pacific; Australia and New Zealand					
Application	Crates; Housewares; Opaque Containers; Small Appliances; Sports, Leisure & Toys					
Market	Consumer Products; Electrical / Electronics					
Processing Method	Injection Molding					
Attribute	Good Heat Aging Resistance; Good Impact Resistance; Good Toughness; High					
	Stiffness: Impact Copolymer					

			Nominal		
Typical Properties			Value	Units	Test Method
Physical					
Melt Flow Rate, (230 °C/2	.16 kg)		5	g/10 min	ASTM D1238
Density			0.90	g/cm³	ASTM D792
Mechanical					
Flexural Modulus			1150	MPa	ASTM D790
Tensile Strength at Yield			25	MPa	ASTM D638
Tensile Elongation at Yield	1		9	%	ASTM D638
Impact					
Notched Izod Impact Strength, (23 °C)			150	J/m	ASTM D256
Thermal					
Deflection Temperature Under Load, (0.46 N/mm ²)			88	°C	ASTM D648

Notes

These are typical property values not to be construed as specification limits.

Company Information

For further information regarding the LyondellBasell company, please visit http://www.lyb.com/.

© LyondellBasell Industries Holdings, B.V. 2017

✓ 0212 659 26 01-02 www.pakrokimya.com.tr

LIIDAZEII

Marking Info@pakrokimya.com.tr

0212 659 26 03

Disclaimer

Before using a product sold by a company of the LyondellBasell family of companies, users should make their own independent determination that the product is suitable for the intended use and can be used safely and legally.

SELLER MAKES NO WARRANTY; EXPRESS OR IMPLIED (INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY WARRANTY) OTHER THAN AS SEPARATELY AGREED TO BY THE PARTIES IN A CONTRACT.

Users should review the applicable Safety Data Sheet before handling the product.

This product(s) may not be used in the manufacture of any of the following, without prior written approval by Seller for each specific product and application:

(i) U.S. FDA Class I or II Medical Devices; Health Canada Class I, II or III Medical Devices; European Union Class I or II Medical Devices;

(ii) film, overwrap and/or product packaging that is considered a part or component of one of the aforementioned medical devices;

(iii) packaging in direct contact with a pharmaceutical active ingredient and/or dosage form that is intended for inhalation, injection, intravenous, nasal, ophthalmic (eye), digestive, or topical (skin) administration;

(iv) tobacco related products and applications, electronic cigarettes and similar devices.

(v) safety components in automotive applications, for example: air bags, air bag unit housings and covers, seat belt mechanisms, brake systems, pedals and pedal supports, steering systems.

The product(s) may not be used in:

(i) U.S. FDA Class III Medical Devices; Health Canada Class IV Medical Devices; European Class III Medical Devices;

(ii) applications involving permanent implantation into the body;

(iii) life-sustaining medical applications.

All references to U.S. FDA, Health Canada, and European Union regulations include another country's equivalent regulatory classification.

In addition to the above, LyondellBasell may further prohibit or restrict the use of its products in certain applications. For further information, please contact a LyondellBasell representative.

Trademarks

Adflex, Adstif, Adsyl, Akoafloor, Akoalit, Alastian, Alathon, Alkylate, Amazing Chemistry, Aquamarine, Aquathene, Avant, Catalloy, Clyrell, CRP, Crystex, Dexflex, Duopac, Duoprime, Explore & Experiment, Filmex, Flexathene, Fueling the power to win, Glacido, Hifax, Hiflex, Histif, Hostacom, Hostalen, Hyperzone, Ideal, Indure, Integrate, Koattro, LIPP, Lucalen, Luflexen, Lupolen, Luposim, Lupostress, Lupotech, Metocene, Microthene, Moplen, MPDIOL, Nerolex, Nexprene, Petrothene, Plexar, Polymeg, Pristene, Prodflex, Pro-fax, Punctilious, Purell, Refax, SAA100, SAA101, Sequel, Softell, Spherilene, Spheripol, Spherizone, Starflex, Stretchene, Superflex, TBAc, Tebol, T-Hydro, Toppyl, Trans4m, Tufflo, Ultrathene, Vacido and Valtec are trademarks owned and/or used by the LyondellBasell family of companies.

Adsyl, Akoafloor, Akoalit, Alastian, Alathon, Aquamarine, Avant, CRP, Crystex, Dexflex, Duopac, Duoprime, Explore & Experiment, Filmex, Flexathene, Hifax, Hostacom, Hostalen, Ideal, Integrate, Koattro, Lucalen, Lupolen, Metocene, Microthene, Moplen, MPDIOL, Nexprene, Petrothene, Plexar, Polymeg, Pristene, Pro-fax, Punctilious, Purell, Sequel, Softell, Spheripol, Spherizone, Starflex, Tebol, T-Hydro, Toppyl, Tufflo and Ultrathene are registered in the U.S. Patent and Trademark Office.

LyondellBasell Technical Data Sheet Date: 8/16/2017