

lyondellbasell

## Moplen HP462R

### Propylene, Homopolymer

#### Product Description

Moplen HP462R is used in extrusion applications. It has a very narrow molecular weight distribution and it is formulated with an anti-gasfading stabilisation package. Moplen HP462R is used in the production of continuous filaments. Typical applications are high-tenacity yarns (HTY) and spunbond nonwovens.

#### Product Characteristics

<b>Status</b>	Commercial: Active
<b>Test Method used</b>	ISO
<b>Availability</b>	Europe, Asia-Pacific, Africa-Middle East
<b>Processing Method</b>	Continuous Filament/Spinning, Spun Bond
<b>Features</b>	Controlled Rheology, Gas-fading Resistant, Homopolymer, Narrow Molecular Weight Distribution
<b>Typical Customer Applications</b>	Nonwoven Spunbond, Filament Yarn, Furniture & Buildings, Geotextile & Agriculture, Hygiene Nonwoven, Protective Clothes, Wipes/Tissues

Typical Properties	Method	Value	Unit
<b>Physical</b>			
Melt flow rate (MFR) (230°C/2.16kg)	ISO 1133	25	g/10 min
Melt volume flow rate (230°C/2.16 kg)	ISO 1133	34	cm <sup>3</sup> /10min
<b>Mechanical</b>			
Tensile Stress at Yield	ISO 527-1, -2	34	MPa
Tensile Strain at Break	ISO 527-1, -2	>50	%
Tensile Strain at Yield	ISO 527-1, -2	10	%
Flexural modulus	ISO 178	1450	MPa
<b>Thermal</b>			
Heat deflection temperature B (0.45 MPa) Unannealed	ISO 75B-1, -2	97	°C
Vicat softening temperature	ISO 306		
(A50 (50°C/h 10N))		151	°C
(B50 (50°C/h 50N))		92	°C

## Notes

Typical properties; not to be construed as specifications.

© LyondellBasell Industries Holdings, B.V. 2010

For the contact details of the LyondellBasell company selling this product in your country, please visit <http://www.lyondellbasell.com/>.

Before using a product sold by one of the LyondellBasell family of companies, users should make their own independent determination that the product is suitable for the intended use and can be used safely and legally. SELLER MAKES NO WARRANTY; EXPRESS OR IMPLIED (INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) OTHER THAN AS SEPARATELY AGREED BETWEEN THE PARTIES IN WRITING. This product(s) may not be used in the manufacture of any US FDA Class III Medical Device or Health Canada Class IV Medical Device and may not be used in the manufacture of any US FDA Class II Medical Device or Health Canada Class II or Class III Medical Device without the prior written approval by Seller of each specific product or application.

Users should review the applicable Material Safety Data Sheet before handling the product.

*Adflex, Adstif, Adsyl, Akoafloor, Akoalit, Alastian, Alathon, Alkylate, Aquamarine, Aquathene, Arconate, Arcopure, Arcosolv, Arctic Plus, Arctic Shield, Avant, Catalloy, Clyrell, CRP, Crystex, Dexflex, Duopac, Duoprime, Duotreat, Filmex, Flexathene, Get in touch with, Glacido, Glidox, Glidsol, Hifax, Histif, Hostacom, Hostalen PP, Hostalen ACP, Ideal, Indure, Integrate, Koattro, LIPP, Lucalen, Luflexen, Lupocomp, Lupolen, Lupolex, Luposim, Lupostress, Lupotech, Metocene, Microthene, Moplen, MPDIOL, Navacet, Nerolex, Nexprene, Petrothene, Plexar, Polymeg, Pristene, Prodflex, Pro-Fax, Punctilious, Purell, SAA 100, SAA 101, Sequel, Softell, Spherilene, Spheripol, Spherizone, Starflex, Stretchene, Superflex, TBAC, Tebol, Tetralol, T-Hydro, Topyl, Trans4m, Tufflo, Ultrathene, Vacido, Valtec, and Winsense* are trademarks owned and/or used by LyondellBasell group companies.

*Akoafloor, Akoalit, Alastian, Alathon, Aquamarine, Arconate, Arcopure, Arcosolv, Arctic Plus, Arctic Shield, Avant, Clyrell, CRP, Crystex, Dexflex, Duopac, Duoprime, Filmex, Flexathene, Glidox, Glidsol, Hifax, Hostacom, Hostalen, Ideal, Indure, Integrate, Koattro, Lucalen, Lupolen, Microthene, Moplen, MPDIOL, Nexprene, Petrothene, Plexar, Polymeg, Pristene, Pro-Fax, Punctilious, Purell, Sequel, Spheripol, Spherizone, Softell, Starflex, Tebol, Tetralol, T-Hydro, Topyl, Tufflo, Ultrathene, and Winsense* are registered in the U.S. Patent and Trademark Office.

Release Date: 22 Oct 2009