

# SIBUR

## Technical Data Sheet PP H120 GP/3 Polypropylene

### PRODUCT DESCRIPTION

**PP H120 GP/3** is a polypropylene homopolymer with standard molecular weight distribution. The product features high fluidity, an optimal stabilization package and balanced physical and mechanical properties.

### TYPICAL APPLICATIONS

**PP H120 GP/3** is a general purpose product. It is used in injection moulding application and for composite materials production.

Physical Property	Test Method	Typical values*
Melt Flow Rate, g/10min. (230°/2.16 kg)	ASTM D 1238	12.0
Density, g/cm <sup>3</sup>	ASTM D 1505	0.90
Mechanical Property		
Tensile strength at yield, MPa (50 mm/min)	ASTM D 638	30
Elongation at yield, % (50 mm/min)	ASTM D 638	10
Elongation at break, % (50 mm/min)	ASTM D 638	>200
Flexural modulus, MPa (5 mm/min)	ASTM D 790	1300
Rockwell hardness, R-scale	ASTM D 785	95
Izod impact strength, J/m (Notched, 23°)	ASTM D 256	26
Thermal Property		
Vicat softening point, °C	ASTM D1525	155

\*Typical values; not for specification

### REACH Statement

Polymers are exempted from registration under REACH. However, the corresponding monomers (used as raw materials for polymer production) and relevant additives have been registered.

**Sibur Holding JSC (and its subsidiaries)** is committed to fully respect REACH legislation and to use only REACH compliant raw materials.

### **Safety**

See MSDS.

### **Technical support**

For any additional information regarding product's characteristics and quality please contact our technical support division using contacts below.

**To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication. Sibur Holding JSC (and its subsidiaries) makes no warranties or representations with respect to the accuracy or completeness of information contained herein and assume no liability for the consequences of its use or in case of misprints.**

**Our products are intended to be sold to industrial and commercial customers. Customers shall test our products to define their suitability for certain customer's purposes. The customer is also responsible for the recycling of our products and their appropriate, safe and legal use.**